



# **INVERTER PRO 2000 UK**

PORTABLE POWER

Generating Sets Range PRESTIGE

#### **PRODUCT ADVANTAGES**

- Ergonomic, light and compact equipment
- Very Silent
- 12 V output
- Quality current
- Low consumption

INVERTER TECHNOLOGY This new, very high performance technology guarantees the stability of the voltage and frequency of your genset to within ± 1% of the nominal value. Such high precision makes it possible to produce high-quality current and supply the most demanding equipment.

12V OUTPUT Supplies equipment operating off 12V and in particular for recharging batteries. Connection cables are included.

#### Range PRESTIGE

Top of the range equipment that is efficient and with low noise emissions, for a wide range of standard requirements.



















# **INVERTER PRO 2000 UK**

#### **GENERAL SPECIFICATIONS**

| Range                                  | PRESTIGE     |
|--|--------------|
| Frequency (Hz)                         | 50 Hz        |
| Max power LTP (kW) *                   | 2            |
| Nominal voltage (V)                    | 230          |
| Number of Phase                        | Single phase |
| Fuel                                   | Petrol       |
| Tank (L)                               | 4.20         |
| 75% cons. (I/h) *                      | 0.90         |
| 75% Autonomy (h) *                     | 4.70         |
| Sound power level guaranteed LwA dB(A) | 89           |
| Acoustic pressure level @1m in dB(A)   | 75           |
| Acoustic pressure level @7m in dB(A)   | 60           |

### **ENGINE SPECIFICATIONS**

| Engine brand       | YAMAHA  |
|--------------------|---------|
| Engine type        | MZ80    |
| Distribution       | O.H.V.  |
| Start              | Starter |
| Oil shutdown       | Oui     |
| Displacement (cm3) | 79      |
| Oil capacity (L)   | 0.40    |

#### ALTERNATOR SPECIFICATIONS

| Technology               | Inverter |
|--------------------------|----------|
| AVR Regulation           | No       |
| Indication of protection | IP 23    |
| Insulation class         | Н        |

#### PLUGS AND PANEL DESCRIPTIVE

1 socket 230V 13A - circuit breaker + 1 socket 12V 12A - circuit breaker ⊦ indicator

#### **DIMENSIONS AND WEIGHT**

| Lenght (cm)     | 49    |
|-----------------|-------|
| Width (cm)      | 28    |
| Height (cm)     | 44.50 |
| Dry Weight (kg) | 21    |

#### **PACKAGING**

| Packaging type                     | Box   |
|------------------------------------|-------|
| Length (cm)                        | 55.50 |
| Width (cm)                         | 36.50 |
| Height (cm)                        | 49.50 |
| Weight (kg)                        | 22    |
| Pallet type                        |       |
| Number of box by pallet            | 12    |
| Pallet height (cm)                 | 103   |
| weight of the packaged Pallet (kg) | 282   |

This product meets the Qualigen charter, which aims to



ensure a high level of quality and guarantee the safety of users. Qualigen: commitment to safety and quality.





# **INVERTER PRO 2000 UK**

### **ACCESSORIES SUPPLIED**



Spark plug spanner



User and maintenance manual

## **OPTIONS**



RYS2

Maintenance kit for YAMAHA MZ80 engine.



RKD1

kit of two diferential removable adapters for domestic sockets. Schema for ground bonding with isolated neutral

