

Product Specifications for 4006-23TAG



Total Power Range

Gross Mechanical Output	531-886 kWm
Typical Electrical Output	595-1000 kVA (476-800 kW _e)
Rated Speed	1500/1800 rpm

50 Hz Typical Electrical Output

Prime	746-802 KVA
Standby	820-898 KVA
Baseload	595-637 kVA

60 Hz Typical Electrical Output

Prime	600-722 kW _e
Standby	660-800 kW _e
Baseload	480-572 kW _e

Emission Standards

Emissions	Fuel Optimised
------------------	----------------

General

Number of Cylinders	6 inline
Bore	160 mm
Stroke	190 mm
Displacement	23 l
Compression Ratio	13.6:1

Aspiration	Turbocharged and air-to-air charge cooled
Combustion System	Direct injection
Rotation from Flywheel End	Anti-clockwise
Cooling System	Liquid
Aftertreatment	-
Typical Alternator Efficiency	90-95%
Switchable	Yes

ElectropaK Dimensions

Length	2927 mm
Width	1690 mm
Height	2125 mm
Dry Weight	2524 kg

Disclaimer

Note 1	*Final dimensions dependent on selected options
---------------	---

Definitions

Prime Power	Unlimited hours usage with an average load factor of 80% of the published prime power over each 24 hours period. A 10% overload is available for
Standby Power	Limited to 500 hours annual usage with an average load factor of 80% of the published standby power rating over each 24 hour period. Up to 300 hours of annual usage may be run continuously. No overload is permitted on standby power.
Baseload	Unlimited hours usage with an average load factor of 100% of the published baseload power. No overload is permitted on baseload power.

4006-23TAG Standard Equipment

Air inlet system

Mounted air filter and turbocharger

Cooling system

Radiator supplied loose incorporating air-to-air charge cooler
System designed for ambients up to 50°C (122°F)
Twin thermostats, water pump

Electrical equipment

24V starter motor, 24V alternator with integral voltage regulator and DC output
High coolant temperature protection switch
Low oil pressure protection switch
Turbine inlet temperature protection

Flywheel and housing

SAE '0' flywheel housing
SAE J620 size 18 flywheel

Fuel system

Digital governing to ISO 8528-5 Class G2 with isochronous capability
Direct fuel injection system with fuel lift pump
Full flow spin-on filters

Lubrication system

Full flow spin-on oil filters
Wet full aluminium sump with filler and dipstick

Optional equipment

4 meter wiring harness
Exhaust counter flanges
Immersion heater
Secondary electric start
Single exhaust outlet pipe
Temperate radiator kit