Cat® C3.3 DIESEL GENERATOR SETS

Standby & Prime: 50 Hz & 60 Hz



Image shown might not reflect actual configuration

Engine Model	Cat® C3.3 Inline 4-stroke Diesel
Bore x Stroke	105.0mm x 127.0mm (4.1in x 5.0 in)
Displacement	3.3 L (201.4 in³)
Compression Ratio	19.25:1
Aspiration	Naturally Aspirated
Fuel Injection System	Inline
Governor	Mechanical


Model	Standby		Prime		Emission Strategy
	50 Hz	60 Hz	50 Hz	60 Hz	
DE33E0	33.0 kVA (26.4 kW)	37.5 kVA (30.0 kW)	30.0 kVA (24.0 kW)	33.8 kVA (27.0 kW)	Low BSFC

PACKAGE PERFORMANCE

Performance	Standby		Prime	
	50 Hz	60 Hz	50 Hz	60 Hz
Frequency	50 Hz	60 Hz	50 Hz	60 Hz
Genset Power Rating	33.0 kVA	37.5 kVA	30.0 kVA	33.8 kVA
Genset power rating with fan @ 0.8 power factor	26.4 kW	30.0 kW	24.0 kW	27.0 kW
Emissions	Low BSFC			
Performance Number	P2490B	P2490A	P2490B	P2490A
Fuel Consumption				
Fuel Tank Capacity, litres (US gal)	161 (42.5)			
100% load with fan, L/hr (gal/hr)	7.7 (2.0)	9.0 (2.4)	7.0 (1.8)	8.1 (2.1)
75% load with fan, L/hr (gal/hr)	5.7 (1.5)	6.8 (1.8)	5.2 (1.4)	6.2 (1.6)
50% load with fan, L/hr (gal/hr)	4.1 (1.1)	5.0 (1.3)	3.8 (1.0)	4.7 (1.2)
Cooling System[1]				
Radiator air flow, m³/min (cfm)	62.6 (2211)	84.8 (2995)	62.6 (2211)	84.8 (2995)
Total coolant capacity, L (gal)	10.2 (2.7)			
Inlet Air				
Max. Combustion Air Intake Restriction, kPa (in H2O)	6.5 (26.1)			
Combustion air inlet flow rate, m³/min (cfm)	2.2 (76)	2.6 (91)	2.2 (76)	2.6 (92)
Max. Allowable Combustion Air Inlet Temp, °C (°F)	50 (122)			
Exhaust System				
Exhaust stack gas temperature, °C (°F)	520 (968)	530 (986)	500 (932)	520 (968)
Exhaust gas flow rate, m³/min (cfm)	5.8 (205)	6.6 (233)	5.7 (201)	6.4 (226)
Exhaust system backpressure (maximum allowable), kPa (in. water)	8.0 (2.4)	10.0 (3.0)	8.0 (2.4)	10.0 (3.0)
Heat Rejection				
Heat rejection to jacket water, kW (Btu/min)	18.0 (1024)	22.0 (1251)	16.0 (910)	18.0 (1024)
Heat rejection to alternator, kW (Btu/min)	3.3 (188)	3.7 (210)	3.3 (188)	3.7 (210)
Heat rejection to atmosphere from engine, kW (Btu/min)	9.3 (529)	9.7 (552)	7.9 (449)	8.2 (466)

Alternator[3]	50 Hz				60 Hz			
Voltages	415V	400V	380V	220V	480V	440V	380V	208V
Motor starting capability @ 30% Voltage Dip, skVA	49	46	42	54	54	46	36	42
Current, amps	46	48	50	87	45	49	57	104
Temperature Rise, °C	125/40							
Frame Size	M1717L4							
Excitation	S.E							

WEIGHTS & DIMENSIONS



Note: General configuration not to be used for installation. See general dimension drawings for detail.

Dim "A" mm (in)	Dim "B" mm (in)	Dim "C" mm (in)	Dry Weight kg (lb)
1540 (60.6)	970 (38.2)	1361 (53.6)	827 (1823)

APPLICABLE CODES AND STANDARDS:

AS1359, CSA C22.2 No100-04, UL142, UL489, UL869, UL2200, NFPA37, NFPA70, NFPA99, NFPA110, IBC, IEC60034-1, ISO3046, ISO8528, NEMA MG1-22, NEMA MG1-33, 2006/95/EC, 2006/42/EC, 2004/108/EC.
Note: Codes may not be available in all model configurations. Please consult your local Cat Dealer representative for availability.

STANDBY: Output available with varying load for the duration of the interruption of the normal source power. Average power output is 70% of the standby power rating. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year.

PRIME: Output available with varying load for an unlimited time. Average power output is 70% of the prime power rating. Typical peak demand is 100% of prime rated ekW with 10% overload capability for emergency use for a maximum of 1 hour in 12. Overload operation cannot exceed 25 hours per year

RATINGS: Ratings are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions.

DEFINITIONS AND CONDITIONS

[1] For ambient and altitude capabilities consult your Cat dealer. Air flow restriction (system) is added to existing restriction from factory.

[2] Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77° F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 BTU/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

[3] UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics. Generator temperature rise is based on a 40° C ambient per NEMA MG1-32.

LET'S DO THE WORK.™

www.Cat.com/electricpower
All rights reserved.
Materials and specifications are subject to change without notice.The International System of Units (SI) is used in this publication.
© 2020 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow", the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission

LEHE2576-01 (10/20)